VETIVER SYSTEM FOR RIVER AND CANAL BANK STABILISATION

Paul Truong

TVNI Technical Director

Email <Paultruong@vetiver.org>

Brisbane, Australia

All materials in this document remain the property of TVNI. Permission must be obtained for their use. Copyright © 2017

Principles of the Vetiver System for River Bank Stabilisation

In flood erosion control and riverbank stabilisation the VS uses the deep and high tensile root system to reinforce the bank slopes and its dense and stiff stems to spread and reduce flow velocity .

- To stabilise the bank steep gradients, horizontal rows planted on approximate contour lines
- To reduce flow velocity of the strong current therefore preventing scouring from the strong flow, planting of cross rows is needed.
- For maximum effect, the cross rows are orientated at right angle to the flow direction.
- *The spacing of both horizontal and cross rows varies with slope gradient and length, soil type, flow velocity and depth .*

Strong current flattened the native grass but not vetiver on this waterway

Indoor flume test



In flume test a mature hedge can bank up water to 600mm depth

STREAMBANK STABILISATION IN AUSTRALIA

Severe erosion on the abutment of the Coolumboola Creek bridge near Miles.

Vetiver planting following repair

Cross rows are most effective when planted right angle to flow direction

One month after planting

Six month after planting

There were several big flows during the first summer and no damages were noted. This abutment is now well protected by these mature vetiver .

18 months after planting

Five years after planting

Dam spillway protection

Six months after planting

25 5 2011

23 5 2001

Eight months after planting

Mekong Delta Vietnam: Protecting bank against wave erosion

Six months after planting

Assam, India : Doria Bridge approach, Note: grid pattern

Two months after planting

Two years after planting

Thank you